

# m'ā' mdok oekāuhs

n<kā. dv k. r i Ndj

n<kā. dv k. r i Ndfō i Ndm; sj k ud úi k&an<kā. dv k. r i Ndj úi k&andú; d l rk . , snj qrfhamy; i oykaj k w; ; j&ahd l ghq=fj kfj kaōj D; ñ, . Kka2010-07-28 Ēk fm'j ' 10'00 ol j&ad ndr. kq efi'

## **Bowser**

Capacity : Sewage – 3.0 m<sup>3</sup>

**Construction** : Steel fabricated with 5 mm sheet metal and 10 mm M.S. plate easily detachable body with anti surge baffles.

**Body Construction** : Mild Steel Fabricated and coated inside with epoxy layer' Outside of the body to be painted with high gloss automotive paint to the design and artwork of our organization.

## **Vacuum pump**

- Air flow capacity @ 60% vacuum : 4500 l/min
- Air flow @ free air : 5300 l/min
- Minimum vacuum : 90%
- Minimum pressure : 1.4 bars
- power required at 0.5bar : rel/kw – 5.8 kw
- Type : Rotary vane type vacuum pump
- Sound level 60% vacuum 7m dis : 76 dBA
- Made by European brand

## **Standard Features:**

- Single 16" manhole, primary & secondary shut off valve
- Sludge trap tank for over load liquid
- Pressure line filter, change over valve discharge silencer
- Access ladder & sight glass at rear door

## **Warranty Period :**

Minimum 1 year warranty against manufacturing defects.

02' . , snj qrh mr&ad l s& i ; sh&okj , fm'j ' 9'00 i g m'j ' 04'00 ol j&ad n, kā. dv k. r i Nd mr&as s& < yel b'

03' fgk&ā új D; l rk wj i adj i oyd wod, wdh; k j , k&hdā; fh l ÷yg i yNd. súh yel '

03' fuu ñ, . Kkab&Bm; al s&fi s u& ; nk , o l j rhl " l j rfhaj 'imi by, fl <j f&ā " . , s nj qrh w; ; j&ahdj i oyd ñ, . Kk&hk&aj kai oyka r , b&dm&Xñ ; em&f, kai Ndm; **Sk. r i Ndj** ' n<kā. dv hk , m&khg , efnk fi afy&aw; k&af. kú; afgk&ā fm&úahg nyd, s&uk&af&hdud < yel b' by; fō, dfj kami j , efnk ñ, . Kkam&ā&ā l rkq efi'

ví'ti'tk&ā' ùri sy"

i Ndm; s

n<kā. dv k. r i Ndj'

ýrl : k wxl h ( 045- 2287275

Ēkh : 2010-06-30

n<kā. dv k. r i Nd l d&hd, fha&h'